




:: FD-10TM :: TECHNICAL SPECIFICATIONS

FOUNDATION SERIES

The FD-10TM is a passive two-way enclosure incorporating a proprietary 10" LF, a high frequency TWT driver in a ported trapezoid style. It can be used as a stage front monitor or as a surround sound cabinet. The FD-10TM has an exceptional transient response and crisp high frequencies.



OUTLINE DRAWING



DESCRIPTIVE DATA

Frequency range ·	45 Hz - 20 kHz	Material/Cabinet ·	5/8" Birch 13 ply
Sensitivity (SPL 1W @ 1m) ·	97 dB	Finish ·	Urethane
Maximum SPL ·	127.8	Grille ·	Perforated metal
RMS (W) ·	300	Connections ·	-
Peak power (W) ·	600	Height (In/cm) ·	21 5/8" / 54.93
Impedance (Ohms) ·	8	Width In/cm) ·	14" / 35.56
Passive crossover ·	3 KHz	Depth (In/cm) ·	13" / 33.02
Dispersion (Horiz./Vert.) ·	Radial	Weight (lbs/Kg) ·	45 / 20.45
High frequencies ·	Biradial/Tweeter	Fixing points ·	9 points
Low frequencies ·	1 x woofer 10"		

SPL VS FREQUENCY

