

.: TH-215H2 :.

TECHNICAL SPECIFICATIONS

THEATRE SERIES

This cabinet has a smart design and impressive driver complement. Its crossover gives great performances in passive mode, and when used with an outboard processor, produces superior sound with little distortion even under extreme demands. It has the features of a top line PA cabinet; 1200 Watts RMS power handling, high sensitivity, extended and smooth LF response, audio coverage, a rich midrange and a smooth extended high end.

OUTLINE DRAWING





DESCRIPTIVE DATA

Frequency range ·	45 Hz - 20 kHz	Material/Cabinet •	5/8" Birch 13 ply
Sensitivity (SPL 1W @ 1m) ·	103 dB	Finish ·	Urethane
Maximum SPL ·	139.8	Grille ·	Perforated metal
RMS (W) ·	1200	Connections ·	-
Peak power (W) ·	2400	Height (In/cm) ·	50 1/8" / 127.32
Impedence (Ohms) ·	4 opt. 8	Width In/cm) ·	21 1/2" / 54.61
Passive crossover ·	1.6 KHz	Depth (ln/cm) ·	18 1/4" / 46.36
Dispersion (Horiz./Vert.) ·	60° x 40° (2")	Weight (lbs/Kg) ·	135 / 61.36
High frequencies ·	2" driver	Fixing points ·	11 points
Low frequencies ·	2 x woofer 15"		

SPL VS FREQUENCY

