


.: TH-218B :. TECHNICAL SPECIFICATIONS

THEATRE SERIES

Extensive research by the TR team led to the development of the TH-218B. It features an extremely compact cabinet with very high power handling and sensitivity. Using twin high power and high efficiency 18" driver, the TH-218B also offers a bass extension down to 34Hz. It can be used with any of the Foundation Series or Series' Theatre top mid/high cabinets or add new life and punch to existing systems. This exceptional 1200W RMS bass cabinet can even withstand the ultimate punishment of raves, mosh pits, and large discos.



OUTLINE DRAWING



DESCRIPTIVE DATA

Frequency range •	34 Hz - 400 kHz (-6 dB)	Material/Cabinet •	5/8" Birch 13 ply
Sensitivity (SPL 1W @ 1m) •	102 dB	Finish •	Urethane
Maximum SPL ·	140.8	Grille ·	Perforated metal
RMS (W) ·	1500	Connections ·	-
Peak power (W) ·	3000	Height (In/cm) ·	21 3/4" / 55.25
Impedence (Ohms) ·	4 opt. 8	Width In/cm) ·	44 3/8" / 112.71
Passive crossover ·	100 Hz	Depth (In/cm) ·	29 1/8" / 73.98
Dispersion (Horiz./Vert.) •	N/A	Weight (lbs/Kg) ·	135 / 61.36
High frequencies •	-	Fixing points ·	-
Low frequencies ·	2 x woofer 18"		

SPL VS FREQUENCY